

Sigen PV Inverter

3.0 – 6.0kW Single Phase



- Easy installation with side cabling
- Visible energy tracking on mySigen APP
- WLAN, Ethernet & 4G communication
- DC/AC ratio up to 2
- Dual MPP trackers
- IP66 protection rating

Sigen PV Inverter 3.0–6.0 kW Single Phase

Sigen PV Max	3.0 SP	3.6 SP	4.0 SP	4.6 SP	5.0 SP	6.0 SP	Units	
DC Input								
Max. PV power	6000	7360	8000	9200	10000	12000	W	
Max. DC input voltage				600				V
Nominal DC input voltage				350				V
Start-up voltage				100				V
MPPT voltage range				50 ~ 550				V
Number of MPP trackers				2				
Number of PV strings per MPPT				1				
Max. input current per MPPT				16				A
Max. short-circuit current per MPPT				20				A
AC Output								
Nominal output power	3000	3680	4000	4600	5000	6000	W	
Max. output apparent power	3300	3680	4400	5000	5500	6600	VA	
Nominal output current	13.6	16.0	18.2	20.9	22.7	27.3	A	
Max. output current	15.0	16.0	20.0	22.7	25.0	30.0	A	
Nominal output voltage				220 / 230 / 240				V
Nominal grid frequency				50 / 60				Hz
Power factor				0.8 leading ~ 0.8 lagging				
Total current harmonic distortion				THDi < 2%				
Efficiency								
Max. efficiency				98.0%				
European efficiency	97.0%	97.1%	97.2%	97.3%	97.4%	97.4%		
General Data								
Dimensions (W / H / D)				700 / 300 / 268				mm
Weight				18				kg
Storage temperature range				-40 ~ 70				°C
Operating temperature range				-30 ~ 60				°C
Relative humidity range				0% ~ 95%				
Max. operating altitude				4000				m
Cooling				Natural convection				
Ingress protection rating				IP66				
Noise emission				< 30				dB
Installation method				Wall-mounted				
Monitoring & Protection								
Anti-islanding protection				Supported				
DC reverse polarity protection				Supported				
Insulation monitoring				Supported				
DC surge protection				Supported				
AC surge protection				Supported				
Residual current monitoring				Supported				
AC overcurrent protection				Supported				
AC short-circuit protection				Supported				
AC overvoltage protection				Supported				